


Shed Building 2.0

Custom 8' by 8' by 8' Shed Plans

Designed for

Sheds of Hope



Shed provided by Local Churches for Sheds of Hope
Designed by ChurchGPS.org
Version 2.0 Build 5.8

Get a Group to Build Sheds

Page 2

Building Sheds for Disaster Victims

Sheds of Hope Teams have built over 1000 sheds for families. You can help during the next disaster. Here's a way that your group can help, whether it's in Oklahoma or your own community.

Any Size Group or Church Can Help

ChurchGPS is providing a free plan to help groups in North Texas and Oklahoma pre-build panels for sheds that can be assembled by teams at the disaster site. The plan will enable you to cut, prepare, and assemble 2, 4, or 6 sheds at a time, depending on how many helpers you can gather. A church parking lot is an ideal location for doing the work. Just build and flat-stack the panels for each shed.

A material list is provided and the church or group can order these materials from their local lumber yards. The idea is to build the sections, floor, walls and roof trusses. These can be shipped flat to OK and assembled on site. You can arrange for Sheds of Hope to pick up and transport the pre-built panels to the site, where volunteers will assemble them on the homeowner's property.

At the moment, we are focusing on Oklahoma, but these plans can be used anywhere.

Step 1. Download a Free PDF Shed Kit instructions from ChurchGPS. This will provide you with...

The material order list for 1, 2, 4 or 6 sheds

Instructions on how to build your shed at your church

Instructions on how to set up the shed at the site

Step 2. Have a fund raiser for the sheds (allow)

Material for 1 Shed allow \$850 + \$150 for pick-up and delivery – total \$1,000

Material for 2 Sheds allow \$1,700 + \$250 for pick-up and delivery – total \$1,950

Material for 4 Sheds allow \$3,400 + \$350 for pick-up and delivery – total \$3,750

Material for 6 Sheds allow \$5,100 + \$450 for pick-up and delivery – total \$5,550 –

This is a full trailer load.

Step 3. Arrange a work day at the church.

10 to 20 people who know what they are doing could build 4 to 6 sheds in a day.

Don't try and do too much in one day.

Organize Teams of 6 to 8 People for Each Shed

1 person to help organize the material during cutting and measuring

1 person to do the cutting (measure twice cut once.) This should only be done by someone who knows what they are doing – This is NOT a training day to help people learn how to use a Miter Saw!!!!!!

1 person reading out the instructions for the people putting the parts together (a seat with an umbrella and cold drink would also be needed for this person)

4 or 5 building the parts for each shed

Tools Needed That Can Be Shared by All Teams

1 Miter Saw (you could set up and share this for all the teams). Remember: This should only be used by someone who knows what they are doing – This is NOT a training day to help people learn how to use a Miter Saw!!!!!!

1 skill saw (at least one for all the teams to share) This should only be used by someone who know what they are doing – This is NOT a training day to help people learn how to use a skill saw!!!!!!

Tools Needed Per Team

Everyone have their own tape measure and pencil

5 drills with battery chargers a #2 driver bit, #20 and #25 Start driver bit

2 hand squares

2 hammers

Chalk line

Level

Before Moving Forward

Make sure you are using the latest version of ChurchGPS.org Shed Instructions.

This is a work in progress. Check the version number on this booklet with the one on www.churchgps.wordpress.com

Let's talk! Share the Love...John Browne

Order List For...

Page 4

1 Shed

Treated Lumber

Flooring

- 2 - 4"x6"x8'
- 10 - 2"x4"x8'
- 2 - 3/4"x4"x8' Treated Ply

IF Optional Step* is Used

- 3 - 2"x4"x8'
- 3 - 2"x2"x8'
- 1 - 2"x4"x10'
- 1 - 2"x6"x10'
- 7 - 8" Joist Hangers

IF Optonal Ramp* is Used

- 4 - 2"x6"x10'
- 3 - 2"x4"x8'
- 5 - 6" Hurricane Ties

Non-Treated Lumber

Walls

- 44 - 2"x4"x8'
- 5 - 2"x4"x10'
- 3 - 2"x2"x8'

LP SmartSide

10mm x4'x8' LP Siding

LP SmartTrim

10 - 1"x4"x16' @ HomeDepot or
14 - 1"x4"x12' @ Lowe's

Roof

- 3 - 7/16"x4"x8'OSB
- 1 Roll of 15lb Roofing Felt
- 2 lbs of Roofing Nails
- 4 - 10' Galv'd Drip Edge
- 3 Bundles Architectural-Slate
- 1 Bundle of 3-Tab - Slate

Shed-in-a-Bucket

- Screws 1-5/8" 500 2lb12ozs
- Screws 2" 350 2lb10ozs
- Screws 2-1/2" 300 4lb10ozs
- Screws 3-1/2" 250 4lb12ozs
- Screws 8x1" 1-box SHP PT
- 6 - 3.5" 'Tee' Hinges Zinc
- 3 - 5" Barrel Bolt Latches
- 10 - 6" Hurricane Ties
- 1 - 7/64 Drill Bits 2PK
- 1 - 2" Metal Power Bit 5PK

Home Depot

SKU# and Quantity

- 0000-259-270 Qty 2
- 0000-167-929 Qty 10
- 0000-261-688 Qty 2

Allow \$135 + Tax

- 0000-167-929 Qty 3
- 0000-302-477 Qty 3
- 0000-124-380 Qty 1
- 0000-124-884 Qty 1
- 0000-102-924 Qty 7

Allow \$40 + Tax

- 0000-124-884 Qty 4
- 0000-167-929 Qty 3
- 0000-102-924 Qty 5

Allow \$44 + Tax

- 0000-161-640 Qty 44
- 0000-161-659 Qty 5
- 0000-165-360 Qty 3

Allow \$145 + Tax

- 0000-509-095 Qty 8

Allow \$210 + Tax

- 0000-117-879 Qty 10

Allow \$160 + Tax

- 0000-386-081 Qty 3
- 0000-258-830 Qty 1
- 0000-193-631 Qty 2
- 0000-566-721 Qty 4
- 0000-779-095 Qty 3
- 0000-304-757 Qty 1

Allow \$160 + Tax

Shed-in-a-Bucket

- 0000-735-034 Qty 1
- 0000-735-064 Qty 1
- 0000-735-068 Qty 1
- 0000-177-313 Qty 1
- 0000-185-175 Qty 1
- 0000-163-241 Qty 6
- 0000-854-339 Qty 3
- 0000-102-924 Qty 10
- 0000-382-093 Qty 1
- 0000-406-605 Qty 1

Allow \$200 + Tax

Lowe's

SKU# and Quantity

- 465463 Qty 2
- 489062 Qty 10
- 471096 Qty 2

Allow \$144 + Tax

- 489062 Qty 3
- 204231 Qty 3
- 489074 Qty 1
- 489100 Qty 1
- 116241 Qty 7

Allow \$40 + Tax

- 489100 Qty 4
- 489062 Qty 3
- 21993 Qty 5

Allow \$44 + Tax

- 6005 Qty 44
- 27172 Qty 5
- 4513 Qty 3

Allow \$150 + Tax

- 55897 Qty 8

Allow \$210 + Tax

- 213235 Qty 14

Allow \$160 + Tax

- 122121 Qty 3
- 10306 Qty 1
- 108149 Qty 2
- 20192 Qty 4
- 10076 Qty 3
- 14624 Qty 1

Allow \$160 + Tax

Shed-in-a-Bucket

- 0 Qty 1
- 8047 Qty 6
- 309005 Qty 3
- 21993 Qty 10
- 351681 Qty 1
- 580687 Qty 1

Allow \$200 + Tax

Helping to Improve the Building Process

Page 5

When you see this **Blue Bar**
across the top of the page this indicates
a **BREAK** in the process.

1. Take a water break...

2. Make notes that may help improve
the building sequence for
yourselves and others

3. When finished with the shed,
please send your
notes and recommendations to
john@ChurchGPS.org

Tools Needed To Pre-Cut Material List

Page 6



2 People who know how to
use a Miter Saw



2 People who know how to
use a Circular Saw

Use All Tools According to the
Guidelines in the Owner's Manual

Start and End with Prayer

Page 7

Give God thanks for

His grace and your ability to work on this project today

Give God thanks for

Safety of all in traveling to get to the site today

Give God thanks for

The weather

Ask God's Blessing on

the people who will receive this shed

Ask God's Blessing on

All who work on this shed and that we will serve each other

Cutting List for ONE (1) Shed - Page 1

Page 8

Get a felt tip black marker and write the name that is underlined on all cut pieces.

Example: "Saw Horse"

Note: Write the Size and Name on the Top Edge of the Board.

This will be very helpful when the team starts to build the parts.

1. To find the top edge of the board, first find the crown (keep the hump of the joist or stud up). If the board is straight, pick an edge.
2. Why? When the team is building the parts, they will see the name and the size on the top edge of each board -- They will know they are using the right part, and they will know they are keeping the boards with the crown up
3. Most importantly - It also means that the writing will be hidden when the shed is built

Treated Lumber

Cut 2 - 4 x 6 96" long Skids



Keep the crown / hump to the top when marking the 45° cuts on each end



Cut each end to these sizes

Treated Lumber

Cut 7 - 2 x 4 92-7/8" long Joists



Cut 2 - 2 x 4 92" long Side Joist Stringers

Cut 1 - 2 x 4 96" long Door End Joist

Cutting List for ONE (1) Shed - Page 2

Page 9

Non-Treated Lumber

Cut 14 - 2 x 4 72-1/2" long Side Wall Studs

Cut 4 - 2 x 4 93-1/2" long Side Top or Bottom Wall Plate

Non-Treated Lumber (Note: cut these out of 2 x 4 x 10')

Cut 4 - 2 x 4 55" long Rafter End

Cut 6 - 2 x 4 55" long Rafter Middle

Mark all of these, and go to page 28 and 29 and cut as needed.

If you do not have a floor constructed yet, use a 4 x 8 sheet of plywood for this step.

Non-Treated Lumber

Cut 9 - 2 x 4 74" long Back/Front Wall Studs

Cut 2 - 2 x 4 75-1/2" long Front Door Jamb

Cut 1 - 2 x 4 89" long Back Wall Bottom Plate

Cut 2 - 2 x 4 96" long Back/Front Wall Top Plate

Cut 2 - 2 x 4 16" long Front Wall Bottom Plate

Cut 1 - 2 x 4 60" long Front Wall Door Header

Non-Treated Lumber


Cut 4 - 2 x 4 72" long Saw Horse

Cut 8 - 2 x 4 23-1/2" Saw Horse Legs (use cutoffs)

Cut 8 - 2 x 4 10-3/8" Saw Horse Braces to the long side

Cut the 8 braces at 20° (use cutoffs)

See Page 11 for more details





Cutting List for ONE (1) Shed - Page 3

Page 10

Non-Treated Lumber

Cut 4 - 2 x 4 at 45°	74-1/2"	long point	<u>Door</u>	
Cut 2 - 2 x 4 at 45°	25"	long point	<u>Door Rt</u>	
Cut 2 - 2 x 4 at 45°	27-1/2"	long point	<u>Door Lt</u>	
Cut 1 - 2 x 4	18"	long	<u>Door Rt Mdl</u>	
Cut 1 - 2 x 4	20-1/2"	long	<u>Door Lt Mdl</u>	



Roof

Cut 2 - 4-5/8" x 96" strips of the side
of a 7/16" x 4' x 8' OSB sheet for each roof

Page 11

Trim

Cut the trim to be shipped with the shed

Cut 2 @ 54" x 3-1/2" then cut 20° on the ends



52-1/2"

Cut 2 @ 76-1/4" x 3-1/2" one end at 20° to the right



Cut 2 @ 76-1/4" x 3-1/2" one end at 20° to the left



Cut 2 @ 54" x 3-1/2" then cut 20° on the ends



52-1/2"

These are all cut with 90° ends

Cut 4 @ 75" x 3-1/2"



Side Corner Trim

Cut 2 @ 94-3/8" x 3-1/2"



Side Top Trim

Cut 2 @ 77" x 3-1/2"



Door Side Trim

Cut 4 @ 76-1/2" x 3-1/2"



Door Trim

Cut 1 @ 64" x 3-1/2"



Door Top Trim 1

Cut 1 @ 63" x 3"



Door Top Trim 2

Cut 3 @ 19-1/2" x 3-1/2"




Door Cut To Fit

Cut 3 @ 19" x 3-1/2"



Door Cut To Fit




Preparation - Note: 2 Saw Horses are Needed for Each Team Building A Shed at the Same Time

Page 12


Make 2 saw horses 23-1/2" high by 6 ft. wide

Materials Needed 4 - 2" x 4" x 8'
Cut 4 - 72" and 8 - 23-1/2" (from cutoffs)
Cut 8 braces as needed (from cutoffs)



Roof and Wall Section Overview

Page 13



Flooring

Page 14


Treated Lumber

Runners 2 - 4" x 6" x 8'

Set runners on saw horses. Cut the ends and mark joists layout from template

Level Saw Horses in both directions before you begin


96"



Floor Joists
Treated Lumber 10 - 2" x 4" x 8"

Side Stringers Cut Two @ 92"
Joists Cut Seven @ 92-7/8"

Mark the joists on the 92" Side Joist Stringers




Attaching the Joists to the Runners

Page 16


2-3/4"

1-1/4"


One 3-1/2" screw on each runner




Door End



Now line up the joists and the runners to the marks and fasten the joists to runners at \wedge with one 3-1/2" screw



Square the frame as needed, making sure it is level
Finish attaching the joists to the frame with one 3-1/2" screw on each side
You will have to angle this screw starting half-way up the joist



Before Flooring

Page 17

2 1/2

With the frame attached to the runners and everything square and level attach a 2" x 4" x 8' to door end secure to runners and joists with 2-1/2" screws pulling each joist together

**Attach One
2" x 4" x 96" Joist at
the Door End**



1 1/4

Attach a Hurricane Tie with 1-1/4" screws to each joist and runner
Keep the ties to the inside along the door end and back wall



Red Bar at the Top means...

Page 18

When you see a **Red Bar** across the top of the page this indicates an **OPTIONAL STEP** in the process

If you DID order the material for the Optional Step or Ramp
Turn to the Step or Ramp page and proceed with the one to be built

If you did NOT order the material for the Optional Step or Ramp
Skip to the next page that does not have a Red Bar along the top

Model with Optional Front Door Step

Page 19

Material needed

Treated

3 / 2" x 4" x 8'

1 / 2" x 4" x 10'

3 / 2" x 2" x 8'

1 / 2" x 6" x 10'


7 / 8" Joist

Hangers


100 / 1 1/4"

screws

Frame with
3" screws and
square before
installing step



Cut as needed and secure a 2" x 2" treated filler on top of each step joist allowing a 1" space behind the step tread




Center the step on the door side - slide the step frame under the floor joists until step is 1 in away from the joist.
Use 6 - 8 in joist hangers to secure the step

Model with Optional Front Door Step


Page 20

Joist hanger locations

Attach to inside of front double joist and the joist furthest back from the front door



Cut and Fasten 2 - 2" x 6" x 56" allowing a 1" over hang along front and sides



Pull step frame tight and make sure it is square to the frame and centered on the door end



Model with Optional Front Door Ramp

Page 21

Material Needed

Treated Lumber

3 / 2" x 4" x 8'


4 / 2" x 6" x 10'

5 / 6" Hurricane Ties

25 / 1 1/4" screws



Allow about a 1/4" for spacing



You don't need to flush this

end as it will be in the ground

Just evenly space the treads

Fasten 8 - 2" x 6" x 56" allowing a
1" over hang along sides to 5 - 48"
joists spaced evenly

Model with Optional Front Door Ramp

Page 22


When attaching the Hurricane Ties to the floor joist
along the front of the door...

First, see the next page to see how to mark the Location of the Hurricane Ties

Then, if the floor is not installed yet - flush the top of the joist
to the top of the Hurricane Tie and secure to the joist with 5 - 1 1/4" screws

Flush the Hurricane Tie to the **top of the floor**

joist or 1/2" below the floor if installed



Note this ramp tread will have to be removed to secure the ramp to the Hurricane Ties on site - Please don't put these screws too deep - leave them at the surface

Provide a ziplock bag and put 60 / 1 1/4" screws and 12 / 3" screws in it
Secure the bag to the underside of the ramp for the
site crew to have the right screws for installing the ramp to the shed


Model with Optional Front Door Ramp

Page 23

This ramp will be attached on the field to the 5 - 6" Hurricane Ties

Have 4 people hold up the ramp and one person get under it and when it is in place mark the joists from below. Remember to Center the Ramp and hold it down the 1" to allow the door to open.

Apply the Hurricane Ties to the side of the building



Take some scrap wood and put it in between the ties to keep people from catching on them while transporting the shed




After the Optional Door Step is secured under the joists, proceed to the flooring

Page 24

Start 3/4" Treated Plywood flooring at door end; flush three sides and screw down with 2-1/2" screws, making sure all screws are set and in the center of the joists



Make sure to have half the joist exposed and that screws do not miss the joist. Give them a little angle.



Let the Treated Plywood overhang, and screw the flooring to the joists. As you fasten last joist, measure to ensure joist and flooring are parallel. Cut off the overhang flush with the joist. Use a chalk line and circular saw.

Floor Joist Direction to Plywood

Page 25

Start Treated Plywood flooring at door end, with the LONG side of the plywood going across the door end; screw down with 2-1/2" screws, making sure all screws are set and in the center of the joists

NOTE Door End has the Double Joist



Floor Joist Direction to Plywood

2 1/2

Sheet 2 -
Let this hang
over and then
trim to fit as
needed (*see
detail below)

Sheet 1 -
Set Door End
First
(The End with
Double Joist)

Flush All Three
Sides



*Let the Treated Plywood overhang, and screw the flooring to the joists. As you fasten last joist, measure to ensure joist and flooring are parallel. Cut off the overhang flush with the joist. Use a chalk line and circular saw.

The Floor is now Complete


Page 26

Leave the floor on the Saw Horses

This will be your workbench for the walls and door

Now that the floor is in place, check the floor for level again

-- I know it was OK the last time, but indulge me.



Helping to Improve the Building Process

Page 27

When you see a **Blue Bar** across the top of the page remember this indicates a **BREAK** in the process.

WATER...Everyone!

Number of people on your team? _____

Your recommended number for the tasks so far would be _____

Look back at the instructions and make any notes that would help others in understanding the process


Other Notes:

Four Hints for Building the Sides

Page 28

1. Slide all the studs and the top or bottom plate to one edge. Fasten all the studs and then slide the wall across to the other side and fasten the studs - It is easier to fasten the screws with the drill at the edge.
2. Use the floor to square the frame.
3. Cut the siding for length before securing to the side walls. This way it is easier to measure the 1-1/2" top and bottom and make sure your screws find a stud.

Bonus Tip: Make a template for the 1-1/2" by taking a 2" x 4" piece of scrap about 18" long and drawing a guide-line 1-1/2" in from the edge. Use a black felt tip marker. Then you can place it against the stud, under the sheet of siding to see how far the overhang should extend.



4. Chalk line at the 1-1/2" mark and cut off the overlap after the siding is secured in place.


Note: these panels can be used on either side of the shed. There is no top or bottom.

Set it to the side after you build it.

Repeat for the other side.


Screw and Cut Diagram - Reference Page

Page 29



When building walls
install and secure “A” first

An Aside: Try to keep the Crown of the joist and studs up. This does two things...



First, for the Floor, the weight will tend to pull the joist down and straighten the joist.

Secondly, for the Walls, this keeps the bend of the wall in the same direction, which in turn will make the wall look straighter and lie flatter on the table while working - If you have one stud bent in one direction and one stud bent in an other direction when looking down the wall it may look like the waves of Troy :)


Build the side walls

Page 30

Follow the layout pattern and allow plywood to over hang top and bottom by 1-1/2."
Cut sides flush with outside of stud.

7 Studs for each side wall 72-1/2"
Top and Bottom wall plate 93-1/2"
Flush end studs; center the others


Overhang plywood siding top and bottom by 1-1/2"



Cut The Gussets For The Roof Trusses

Page 31

Use the piece that is the cut-off after building the side walls
(It is approximately 17 3/8" long by 48")




This part is used for the Side Wall

This part is
the cut-off

Take the cut-off section
approximately 17 3/8" wide
and use this for making the
Roof Truss Gussets

You will need 8 Gussets



Note: When fixing the
gussets to the trusses
hold down top edge
about 1/4"

Build The End Roof Trusses Next

Page 32

End Trusses: Put a mark on the floor at the center and 18" from the back end.

NOTE: Flush the rafter ends, and apply one 8" gusset to one side only.

Hold it up 1/2"

Helpful for Site Team

Mark and Square a line up from the bottom of the truss on each side at 3"


Build 2 End Trusses

18"

Center line

Apply ONE 8" gusset to ONE side ONLY
of end trusses

Secure gusset with glue and 1-1/4" screws as needed
(suggestion 6 on each side)



Build The Center Roof Trusses Next


Page 33

Center Trusses: Put a mark on the floor at 19-1/8" from the back end.
NOTE: Flush the rafter ends and apply one 8" gusset to one side; flip over
and apply another 8" gusset to the other side only.

Helpful for Site Team

Hold it up 2"

Mark and Square a line up from the
bottom of the truss on each side at 3"



Now for the back

Page 34


Cut and lay out wall to back wall pattern

Cut rafters and have them ready, the short filler to cover the joint above the wall plate is cut as needed.

5 Studs for back wall 74"


Top wall plate 96" and bottom wall plate 89"

Flush end studs on bottom wall plate; center the others



Apply the Siding

Page 35



Hold over 1-1/2"

Measure down from top 17-1/2"
chalk line to top middle and cut
Repeat for other side

Edge of siding
because of overlap is...



Remove Back Section and get ready for the Front

Helping to Improve the Building Process

Page 36

When you see a **Blue Bar** across the top of the page remember this indicates a **BREAK** in the process.

WATER...Everyone!

Number of people on your team? _____

Your recommended number for the tasks so far would be _____


Look back at the instructions and make any notes that would help others in understanding the process

Other Notes:

Now To The Door End Frame

Page 37

4 Studs for door wall 74"
2 Studs for door wall 75-1/2"
Top wall plate 96" and Bottom wall plate 2 @ 16"
Flush end studs on Bottom wall plate




Make door brace to be removed on site

Page 38


Fasten a 96" stud once the frame is built to hold the ends and the door opening at 54".

Note this board will be removed on site.



Set door stops


Page 39




Now To The Doors

Page 40

Use 2" x 4" studs



Predrill and screw miter corners with 3-1/2" and 2-1/2" screws



Set in the Doors


Page 41

Cut from scrap trim

5/8" spacers

Put a number of 5/8" spacers around the door to center the door in the opening


Make sure the doors are pushed up to the top
with the 5/8" spacers in place



With the Doors in Place, Put on A and B

Edge of siding because of overlap is

Page 42



B

77

Before Cutting out the Doors

REMEMBER to SET the SAW DEPTH to the THICKNESS

of the Siding. If you don't, you will undo your hard work!!

27

27

27

A

17-1/2"


Cut Siding Ad and Bd for Doors

Page 43

Screw siding onto door frame, making sure you get screws into all the cross rails and down both sides of the joint in the middle.

Cut a 1/2" space down the sides and along the top and middle.

If you are adding the Optional Ramp, cut 1-1/2" off the bottom of the door before you hinge and trim the door




Trim Around Door and Door Frame

Page 44

Header is doubled to help water drip off and not go in the top of door.
Caulk along the top and fill any grooves so water can't go behind trim.

Install three 8" T hinges on each side and lock

Looking from the bottom, put the hinges in the right and left side ,
making sure hinge screws are going into the 2" x 4" door frame.



Helping to Improve the Building Process

Page 45

Last Blue Bar for this Section

WATER...Everyone!

How long did it take your team to
get to this point? _____

Number of people on your team? _____


Your recommended number for this
task would be _____

Look back at the instructions and make
any notes that would help
others in understanding the process

Please send your notes and suggestions to John@ChurchGPS.org

Sheds of Hope


Site Set Up



If a Step is Part of the Floor

Page 47

**NOTE: DO NOT USE THE STEP DURING SET-UP
AS IT NEEDS THE SUPPORT OF THE BUILDING
TO WORK**




Set floor on blocks and adjust
Level front to back and side to side

Install Side Wall 1

Page 48

Install side wall, securing the wall along the floor

Brace the wall at back to keep from falling




Install Side Wall 2

Page 49

Install side wall securing the wall along the floor

Brace the wall at back to keep from falling




Install Front Wall 3

Page 50

Use the back opening to get inside once the frame is secured at the corners and along the floor.

Remove the two screws on the outside above and below the lock.

These screws will be near the edge of the trim.



Remove the transportation braces that held the door at the right width. Use one or both of these to prop the door open so that it does not get blown by the wind. After the trim is installed, you will attach a latch to the side trim to hold the door in an open position.

Install Back Wall 4


Page 51

Remove side wall braces.

Lift back wall into place and secure at corners and along the floor.

Use the front door to get inside.


DO NOT USE STEP YET



Install Trusses

Page 52


Keep Trusses in line with Wall Studs.
Secure with screws.



Install Decking 1 and 2

Page 53


Keep trusses aligned.
Install decking 1 and 2
4-5/8" x 96" strip and 48" x 96" sheet



Install Decking 3 and 4 Next

Page 54

Install decking 3 and 4
4-5/8" x 96" strip and 48" x 96" sheet
Repeat 1 and 2



Helping to Improve the Building Process

Page 55

WATER...Everyone!

How long did it take your team to
get to this point? _____

Number of people on your team? _____

Your recommended number for this
task would be _____

Look back at the instructions and make
any notes that would help
others in understanding the process

Other Notes:

Install Roofing Felt Next


Page 56

#1. Roll Felt out; flush and nail on all four sides

#2. Roll Felt out; flush and nail on all four sides

#3. Roll Felt out over the ridge; center and over lap #1 and #2; move into position by flushing the ends and nail all four sides.

Use extra nails as needed to hold paper in place until shingles are installed



Drip Edge After the Roofing Felt

Page 57

Put 4-1/2" or similar wide Galvanized Drip all

the way around the shed

4 - 10' lengths would be needed,

as well as tin snips

Note: If you do this step,

Put Felt on First,

Then Put Drip Edge Over the Felt

DO NOT USE THE STEP DURING SET-UP




To Continue Roofing

Page 58

USE A 3-TAB STARTER SHINGLE


TURN THE SHINGLE WITH THE TABS UP - ALIGN THE TAB-LESS EDGE NO MORE THAN 1" OVER
EDGES OF PLYWOOD DECKING, OR 1/4" OVER DRIP EDGE IF USED -
SECURE WITH NAILS ALONG THE BLACK TAR LINE



THE REASON FOR THE STARTER SHINGLE IS TO PREVENT RAIN FROM GETTING TO THE DECKING
WHERE THE TWO ARCHITECTURAL SHINGLES MEET


After the starter shingle is in place - Start shingling
with a Full Architectural Shingle by holding the
bottom and edge of the shingle to the bottom and
edge of the starter shingle

Note: Cut the 3-tab shingle as
needed BUT KEEP THE CUT
END TO THE INSIDE




Continue Roofing


Page 59



Nail about 1/2" ABOVE the white line



Note: When nailing the shingle at each end of each row, keep the last nail back about 3" to 4" from the end



Hold shingles over edges no more than 1"
or 1/4" if using Drip Edge

Shingle Lap

Bottom of shingle you are nailing
comes to the top edge of lap
giving a 3D effect





Continue Roofing

Page 60

Cutting Ridge

It takes about seven 3-tab shingles,
each trimmed as illustrated below.




It is easier to cut shingles if you turn the shingle over and make the cuts from the back side

Note nail position




Install Trim Around the Front

Page 61



Install Trim Around the Back


Page 62



Install Trim on Both Sides

Page 63

Now you can use the step
to step up into the shed



Praise the Lord!

Shed provided by Local Churches and Sheds of Hope.
We encourage you to seek out a local church in your area.
Shed Designed by ChurchGPS.org

Helping to Improve the Building Process

Page 64

WATER...Everyone!

How long did it take your team to
get to this point? _____

Number of people on your team? _____

Your recommended number for this
task would be _____

Look back at the instructions for
this section and make any
notes that would help others in
understanding the process

Other Notes:

Please send your notes and suggestions to John@ChurchGPS.org